

# Package: dtmapi (via r-universe)

November 18, 2024

**Title** Fetching Data from the 'Displacement Tracking Matrix'

**Version** 0.0.2

**Description** Allows humanitarian community, academia, media, government, and non-governmental organizations to utilize the data collected by the 'Displacement Tracking Matrix' (<<https://dtm.iom.int>>), a unit in the International Organization for Migration. This also provides non-sensitive Internally Displaced Person figures, aggregated at the country, Admin 1 (states, provinces, or equivalent), and Admin 2 (smaller administrative areas) levels.

**URL** <https://github.com/Displacement-Tracking-Matrix/dtmapi-R>,  
<https://displacement-tracking-matrix.github.io/dtmapi-R/>

**License** MIT + file LICENSE

**Encoding** UTF-8

**Roxygen** list(markdown = TRUE)

**RoxygenNote** 7.3.2

**Imports** httr2, jsonlite, magrittr

**Suggests** knitr, rmarkdown, testthat (>= 3.1.0)

**VignetteBuilder** knitr

**Config/pak/sysreqs** libssl-dev

**Repository** <https://displacement-tracking-matrix.r-universe.dev>

**RemoteUrl** <https://github.com/displacement-tracking-matrix/dtmapi-r>

**RemoteRef** HEAD

**RemoteSha** 894b5954d1f6d61b4aa191fa04a7302de7728742

## Contents

get_all_countries . . . . .	2
get_all_operations . . . . .	2
get_idp_admin0_data . . . . .	3
get_idp_admin1_data . . . . .	4
get_idp_admin2_data . . . . .	5

**Index**[7](#)

---

get\_all\_countries      *Fetch All Countries*

---

**Description**

Retrieve all countries for which DTM data is publicly available through the API.

**Usage**

```
get_all_countries()
```

**Value**

A data frame containing the list of all countries.

**Examples**

```
# Fetch all countries
countries_df <- get_all_countries()
head(countries_df)
```

---

get\_all\_operations      *Fetch All Operations*

---

**Description**

Retrieve all operations for which DTM data is publicly available through the API.

**Usage**

```
get_all_operations()
```

**Value**

A data frame containing the list of all operations.

**Examples**

```
# Fetch all operations
operations_df <- get_all_operations()
head(operations_df)
```

---

get\_idp\_admin0\_data     *Fetch IDP Admin0 Data*

---

### Description

Retrieve IDP data at Admin 0 level based on specified parameters. At least one of the following parameters must be provided: Operation, CountryName, or Admin0Pcode.

### Usage

```
get_idp_admin0_data(  
  Operation = NULL,  
  CountryName = NULL,  
  Admin0Pcode = NULL,  
  FromReportingDate = NULL,  
  ToReportingDate = NULL,  
  FromRoundNumber = 0,  
  ToRoundNumber = 0  
)
```

### Arguments

Operation	Optional; Name of the DTM operation for which the data was collected.
CountryName	Optional; Name of the country where the data was collected.
Admin0Pcode	Optional; Country code (ISO 3166-1 alpha-3).
FromReportingDate	Optional; Start date for the reporting period (format: 'YYYY-MM-DD').
ToReportingDate	Optional; End date for the reporting period (format: 'YYYY-MM-DD').
FromRoundNumber	Optional; Starting round number for the data collection range.
ToRoundNumber	Optional; Ending round number for the data collection range.

### Value

A data frame containing the IDP Admin0 data matching the specified criteria.

### Examples

```
# Fetch IDP data at Admin Level 0  
idp_admin0_df <- get_idp_admin0_data(CountryName='Ethiopia', FromRoundNumber=1, ToRoundNumber=10)  
head(idp_admin0_df)
```

---

```
get_idp_admin1_data    Fetch IDP Admin1 Data
```

---

### Description

Retrieve IDP data at Admin 1 level based on specified parameters. At least one of the following parameters must be provided: Operation, CountryName, or Admin0Pcode.

### Usage

```
get_idp_admin1_data(
  Operation = NULL,
  CountryName = NULL,
  Admin0Pcode = NULL,
  Admin1Name = NULL,
  Admin1Pcode = NULL,
  FromReportingDate = NULL,
  ToReportingDate = NULL,
  FromRoundNumber = 0,
  ToRoundNumber = 0
)
```

### Arguments

Operation	Optional; Name of the DTM operation for which the data was collected.
CountryName	Optional; Name of the country where the data was collected.
Admin0Pcode	Optional; Country code (ISO 3166-1 alpha-3).
Admin1Name	Optional; Name of level 1 administrative boundaries.
Admin1Pcode	Optional; Place code of level 1 administrative boundaries.
FromReportingDate	Optional; Start date for the reporting period (format: 'YYYY-MM-DD').
ToReportingDate	Optional; End date for the reporting period (format: 'YYYY-MM-DD').
FromRoundNumber	Optional; Starting round number for the data collection range.
ToRoundNumber	Optional; Ending round number for the data collection range.

### Value

A data frame containing the IDP Admin1 data matching the specified criteria.

### Examples

```
# Fetch IDP data at Admin Level 1
idp_admin1_df <- get_idp_admin1_data(CountryName='Sudan', Admin1Name="Blue Nile")
head(idp_admin1_df)
```

---

get\_idp\_admin2\_data     *Fetch IDP Admin2 Data*

---

### Description

Retrieve IDP data at Admin 2 level based on specified parameters. At least one of the following parameters must be provided: Operation, CountryName, or Admin0Pcode.

### Usage

```
get_idp_admin2_data(
  Operation = NULL,
  CountryName = NULL,
  Admin0Pcode = NULL,
  Admin1Name = NULL,
  Admin1Pcode = NULL,
  Admin2Name = NULL,
  Admin2Pcode = NULL,
  FromReportingDate = NULL,
  ToReportingDate = NULL,
  FromRoundNumber = 0,
  ToRoundNumber = 0
)
```

### Arguments

Operation	Optional; Name of the DTM operation for which the data was collected.
CountryName	Optional; Name of the country where the data was collected.
Admin0Pcode	Optional; Country code (ISO 3166-1 alpha-3).
Admin1Name	Optional; Name of level 1 administrative boundaries.
Admin1Pcode	Optional; Place code of level 1 administrative boundaries.
Admin2Name	Optional; Name of level 2 administrative boundaries.
Admin2Pcode	Optional; Place code of level 2 administrative boundaries.
FromReportingDate	Optional; Start date for the reporting period (format: 'YYYY-MM-DD').
ToReportingDate	Optional; End date for the reporting period (format: 'YYYY-MM-DD').
FromRoundNumber	Optional; Starting round number for the data collection range.
ToRoundNumber	Optional; Ending round number for the data collection range.

### Value

A data frame containing the IDP Admin2 data matching the specified criteria.

**Examples**

```
# Fetch IDP data at Admin Level 2
idp_admin2_df <- get_idp_admin2_data(Operation='Yemen conflict', CountryName="Yemen")
head(idp_admin2_df)
```

# Index

`get_all_countries`, [2](#)  
`get_all_operations`, [2](#)  
`get_idp_admin0_data`, [3](#)  
`get_idp_admin1_data`, [4](#)  
`get_idp_admin2_data`, [5](#)